

LK6P44-B

These new P-series forklifts have a narrow axle with a tighter turning radius enabling the unit to perform sharper turns. The narrow width allows the unit to squeeze into smaller aisles and spaces.



7135 Islington Ave
Woodbridge, Ontario
L4L 1V9 Canada
Tel. (905) 851-3988
Fax (905) 851-6396

THE INDUSTRY LEADER IN ROUGH TERRAIN FORKLIFTS!

LIFTKING®

"P" SERIES SPECIFICATIONS

MODEL	LK6P44	LK8P44
Capacity 61 cm (24") Load Center	6000 lbs (2722 kg)	8000 lbs (3629 kg)
Diesel Engine/Gross H.P.	PERKINS 4 Cylinder Model 1004/86 hp Optional 4 Cylinder Turbo 1004-T/110 hp	
Transmission	3 Speed Powershift	
Travel Speed	20 mph / 32.18 km approximately	
Axles	Heavy Duty Planetary Steer Type	
Drive System	Full Time - 4WD Optional Transmission Disconnect	
Steering	2WS, 4WS, Crab	
Brakes	4 Wheel Hydraulic Fully Enclosed Wet Disc	
Tires	16.9 x 24 10 ply Tubeless	
Hydraulic System	Main Pump 30 gal / min (113.56 L / min) Steering Pump 6 gal / min (22.71 L / min) Return Filter 25 micron replaceable element	
Electrics	12 Volt 1000 CCA Battery	
Fluid Capacities	18.80 L (16.50 Imp. Quarts)	
Cooling System	18.80 L (16.50 Imp. Quarts)	
Crankcase	7.96 L (7 Imp. Quarts)	
Fuel	118.20 L (26 Imp. Gallons)	
Hydraulic	124.50 L (27.40 Imp. Gallons)	
Transmission	14.80 L (13 Imp. Quarts)	
Axle	10.60 L (9.30 Imp. Quarts)	
Dimensions of Unit		
Overall Length (less forks)	155" / 3939 mm	160" / 4064 mm
Overall Width	83.5" / 2120.90 mm	96" / 2438.40 mm
Ground Clearance	18" / 457.20 mm	18" / 457.20 mm
Turning Radius	152.5" / 3873 mm	174" / 4419.60 mm
Fork Dimensions (TxWxL)	2x4x48" / 51x101x1219 mm	2x5x48" / 51x127x1219 mm
Mast	Heavy Duty 2-Stage Roller	
Lift Height	Varies	
Lowered Height	Varies	
Tilt Forward	40 degrees	25 degrees
Tilt Rear	12 degrees	12 degrees
Carriage	48" / 1219.20 mm	60" / 1524 mm
Service Weight (no load)	Approx. 13500 lbs / 6123.50 kg	Approx. 15800 lbs / 7166.80 kg



Full Suspension Seat



Unobstructed Walkway



Easy Access for Repairs



Full Instrument Package



Maximum Ground Contact and Traction

STANDARD EQUIPMENT

Safety Chart	Powershift Transmission	Hour Meter	Ammeter
Oil Pressure Gauge	Engine Temperature Gauge	Transmission Temperature Gauge	Hydrostatic Power Steering
Horn	12 Volt Heavy Duty Batteries	Antifreeze	Fenders
Overhead Canopy	Back Up Alarm	Dry Type Air Cleaner	Block Heater
Manifold Heater	Seat Belt	Hydraulic Oil Immersed Brakes	

OPTIONAL EQUIPMENT

Load Leveler Frame	All Steel Cab with Safety Glass	Turn Signals	Load Clamps
Side Shift	Front & Rear Wipers, Heater and Defroster Fan	Engine Precleaners	Auxiliary Air Compressor
Hydraulic Fork Positioner	Buckets	Turbocharged Engine	Air Filter Indicator



7135 Islington Avenue
Woodbridge, Ontario, Canada, L4L 1V9
Tel: (905) 851-3988
Fax: (905) 851-6396
info@liftking.com

Your local authorized dealer